


GUTEX Thermowall NF - dim. 180 x 60 cm
GUTEX Thermowall NF - Dim. 180 x 60 cm


Lambda	0.040
I-I / BKZ	E/RF3 cr
kg / m ³	160
kPa	≥ 100

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	Pces / paq. <i>Stk / Pak.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
15.179	60 mm		1780 x 580	34	36.72	22.90


utilisable sur ossature en bois, épaisseur 60 mm uniquement / *Holzständer einsetzbar, Hinweis: nur Dicke 60 mm*
 rainure et crête sur le pourtour / *Nut und Falz allseitig*


GUTEX Thermowall GF - dim. 130 x 60 cm
GUTEX Thermowall GF - Dim. 130 x 60 cm


Lambda	0.043
I-I / BKZ	E/RF3 cr
kg / m ³	185
kPa	≥ 150

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	Pces / paq. <i>Stk / Pak.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
11.226	40 mm		1276 x 576	108	84.24	17.00
11.227	60 mm		1276 x 576	72	56.16	25.30


utilisable sur ossature en bois, épaisseur 60 mm uniquement / *Holzständer einsetzbar, Hinweis: nur Dicke 60 mm*
 rainure et crête sur le pourtour / *Nut und Falz allseitig*


GUTEX Thermowall - dim. 130 x 60 cm
GUTEX Thermowall - Dim. 130 x 60 cm


Lambda	0.040
I-I / BKZ	E/RF3 cr
kg / m ³	160
kPa	≥ 100

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	Pces / paq. <i>Stk / Pak.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
14.820	80 mm		1276 x 576	54	42.12	32.70
16.029	100 mm		1276 x 576	44	34.32	40.80
16.032	120 mm		1276 x 576	36	28.08	49.20
16.033	140 mm		1276 x 576	32	24.96	57.40
16.034	160 mm		1276 x 576	28	21.84	65.30


utilisable sur ossature en bois / *Holzständer einsetzbar*
 rainure et crête sur le pourtour / *Nut und Falz allseitig*


GUTEX DW - dim. 255 x 60 cm
GUTEX DW - Dim. 255 x 60 cm


Lambda	0.040
I-I / BKZ	E/RF3 cr
kg / m ³	150
kPa	≥ 100

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	Pces / paq. <i>Stk / Pak.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
17.628	40 mm		2476 x 576	54	82.62	11.90
17.629	60 mm		2476 x 576	36	55.08	17.10
17.630	80 mm		2476 x 576	24	36.72	22.90
17.631	100 mm		2476 x 576	20	30.60	28.50


rainure et crête sur le pourtour / *Nut und Falz allseitig*


GUTEX DW+ - dim. 255 x 60 cm
GUTEX DW+ - Dim. 255 x 60 cm


Lambda	0.042
I-I / BKZ	E/RF3 cr
kg / m ³	200
kPa	≥ 200

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	Pces / paq. <i>Stk / Pak.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
17.623	40 mm		2476 x 576	54	82.62	14.60
17.624	60 mm		2476 x 576	36	55.08	21.90

rainure et crête sur le pourtour / *Nut und Falz allseitig*



Lambda 0.036
I-I / BKZ E/RF3 cr
kg / m³ 50

GUTEX Thermoflex - dim. 135 x 57.5 cm
GUTEX Thermoflex - Dim. 135 x 57.5 cm

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Pces / paq. <i>Stk / Pak.</i>	Pces / pal. <i>Stk / Pal.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
11.131	40 mm		8	112	86.94	6.70
11.132	60 mm		8	72	55.89	9.60
11.133	80 mm		6	56	43.47	12.30
11.135	100 mm		4	42	32.60	15.00
11.134	120 mm		4	36	27.95	17.70
11.136	140 mm		4	32	24.84	20.50
11.137	160 mm		3	28	21.74	23.50
11.138	180 mm		3	24	18.63	26.60
11.139	200 mm		2	20	15.53	32.00
14.647	220 mm		2	20	15.53	34.20
17.493	240 mm		2	16	12.42	37.30



Lambda 0.042
I-I / BKZ E/RF3 cr
kg / m³ 160
NM/m³ ≤ 30

GUTEX Thermofloor - dim. 120 x 60 cm
GUTEX Thermofloor - Dim. 120 x 60 cm

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Pces / paq. <i>Stk / Pak.</i>	Pces / pal. <i>Stk / Pal.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
11.149	21/20 mm			180	129.60	7.60
11.150	31/30 mm			120	86.40	11.60



Lambda 0.046
I-I / BKZ E/RF3 cr
kg / m³ 260
kPa ≥ 100

GUTEX Happy Step - dim. 86 x 59 cm
GUTEX Happy Step - Dim. 86 x 59 cm

Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Pces / paq. <i>Stk / Pak.</i>	Pces / pal. <i>Stk / Pal.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
11.130	6 mm		20	640	324.74	3.30



Lambda 0.048
I-I / BKZ E/RF3 cr
kg / m³ 250
kPa ≥ 100

GUTEX Standard N - panneau de fibre de bois mou - dim. 250 x 100 cm
GUTEX Standard N - Holzweichfaser-Platte - Dim. 250 x 100 cm


Art. Nr.	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Pces / paq. <i>Stk / Pak.</i>	Pces / pal. <i>Stk / Pal.</i>	m ² /palette <i>m²/Palette</i>	Fr./m ²
17.077	8 mm			130	325.00	3.10
17.078	10 mm			100	250.00	3.70
17.079	12 mm			80	200.00	4.30
17.080	15 mm			70	175.00	5.50
17.584	18 mm			55	137.50	6.60



ISOBLOW Standard Plus - machine à insuffler *ISOBLOW Standard Plus - Einblasmaschine*



Art. Nr.	Indiqué pour zum einblasen von	Sac / heure Sack / Stunde	Fr./pce Fr./Stk
13.928	cellulose / <i>Zellulose</i> laine minérale / <i>Mineralwolle</i> perles EPS / <i>EPS Perlen</i> Fibres de bois / <i>Holzfaseren</i>	40-55	17'500.00



KNAUF - isolation à insuffler *KNAUF - Einblasdämmung*



Lambda 0.034
I-I / BKZ A1/RF1

Art. Nr.	Désignation Bezeichnung	Spécification Spezifikation	kg/sac kg/Sack	Sac/palette Sack/Palette	Fr./sac Fr./Sack
16.936	SUPAFIL	Timberframe laine de verre <i>Timberframe Glaswolle</i>	16.60	26	48.15
17.458	SUPAFIL	Cavity wall laine de verre <i>Cavity wall Glaswolle</i>	16.60	26	48.15
17.019	PROTECTFILL	Timberframe laine de verre <i>Timberframe Glaswolle</i>	12.50	28	23.75



Lambda 0.038
I-I / BKZ A1/RF1



ISOCELL - isolation à insuffler en flocons de cellulose *ISOCELL - Einblasdämmung aus Zellulose*



Lambda* 0.037
Lambda** 0.038
I-I / BKZ <100 mm E/RF3 cr
I-I / BKZ >100 mm E/RF2

Art. Nr.	Désignation Bezeichnung	Spécification Spezifikation	kg/sac kg/Sack	Sac/palette Sack/Palette	Fr./sac Fr./Sack
11.169*		flocons de cellulose <i>Zellulosefasern</i>	12.50	21	18.75
18.429**	Evolution	flocons sans sel de Bore <i>Zellulosefasern ohne Borsalz</i>	12.50	21	18.80




GUTEX - isolation à insuffler en fibres de bois *GUTEX - Einblasdämmung aus Holzfaseren*




Lambda 0.038
I-I / BKZ E/RF3 cr

Art. Nr.	Désignation Bezeichnung	Spécification Spezifikation	kg/sac kg/Sack	Sac/palette Sack/Palette	Fr./sac Fr./Sack
14.794	Thermofibre		15.00	21	16.50



SAGER - isolation à insuffler Sagex nero pearl *SAGER - Einblasdämmung Sagex nero pearl*



Lambda 0.033
I-I / BKZ E/RF3 cr

Art. Nr.	Désignation Bezeichnung	Spécification Spezifikation	lt/sac lt/Sack	Sac/palette Sack/Palette	Fr./sac Fr./Sack
16.922		perles 4 - 6.5 mm <i>Perlen 4 - 6.5 mm</i>	500.00		175.00